

emco Bau

emco DIPLOMAT Original SPIN®Safe With ribbed carpet insert 12 SPIN /R

Model 12 SPIN/R

Load Normal to heavy

Support chassis Reinforced support chassis made using rigid aluminium with

sound absorbing insulation on the underside

Approx. height (mm) 15.9

Tread surface Recessed, robust, weather-proof coarse-fibre ribbed carpet

strips (brand-name fibres) for even better dirt removal.

Combined with stainless steel tiles for optimum way

guidance for the blind in the entrance area.

Standard profile clearance approx.

(mm)

5 mm, rubber spacers

Slip-resistance of the insert: R11, slip-resistance of the

stainless steel tiles: R10 (in accordance with DIN 51130)

Colours Anthracite no. 200

Connection Plastic-coated steel cable

Warranty 4 year warranty

Warranty conditions are available at:

Colour fastness to artificial light ISO

105-B02

good 6

Colour fastness to rubbing ISO 105

X12

good 4

Colour fastness to water ISO 105 E01 good 5

Solodi lastiless to water 100 103 Eur 9000

Dimensions Mat width:....mm (bar length)

Mat depth:....mm (walking direction)

Contact emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-

49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·

www.emco-bau.com