





The tactile guidance system for the very highest standards in design and functionality.



Indoor and covered outdoor areas (zones 1 and 2)

Description

Roll-up, hard-wearing entrance mat for supported or self-supporting laying. Fitted with small (122 mm) or large (300 mm) stainless steel tiles for tactile guidance. Each tile occupies three aluminium profile bars. Mat is produced to fit width perfectly; depth obtained using spacing increments of 100 mm. Option of dimpled tiles for attention panel.









Outside (Zone 1)

hair, sand, ash, textile fibres, small leaves and twigs, loose chippings, coarse sand,

Street dust,

small gravel particles

The emco entrance mat as a guidance system for the visually impaired

R 11 slip resist tance as per e DIN 51130

5 years guarantee




Approx. height (mm)	20.9	Accessories
Roll-over and drive-over capability:	Wheelchairs	emco installation frame 500: 500-25 AL Aluminium
	Prams	emco installation frame 500: 500-25 CN Chrome-nickel steel (V2A)
	hand trolleys	emco LUMINA: LUMINA + LED Aluminium
	Light shopping trolleys	emco cover strip: C22 Chrome-nickel steel (V2A)
	Sack-/hand truck	emco dirt collection well: 5000 AL Aluminium
	pallet trucks	emco dirt collection well: 5000 CN Chrome-nickel steel (V2A)
	Electric lift truck	emco dirt collection well: 5000 AL+ Aluminium
		emco dirt collection well: 5000 CN+ Chrome-nickel steel (V2A)
	Cars	emco dirt collection well: 5022 AL Aluminium
Standard profile clearance approx. (mm)	5 mm, rubber spacers	emco dirt collection well: 5022 CN Chrome-nickel steel (V2A)
Connection	Plastic-coated steel cable	emco dirt collection well: 5022 AL+ Aluminium
Max. width/profile length for individual section (mm):	1200	emco dirt collection well: 5022 CN+ Chrome-nickel steel (V2A)
		emco dirt collection well: 5022 AL Aluminium
Profile width (mm)	28.65	emco dirt collection well: 5022 CN Chrome-nickel steel (V2A)
Depth/walking depth		emco dirt collection well: 5022 AL+ Aluminium
for individual section	800	emco dirt collection well: 5022 CN+ Chrome-nickel steel (V2A)
(mm): Weight (kg/m^2)	27,7	emco dirt collection well: 5000 AL Aluminium
Weight (kg/m²) Support chassis	Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside	emco dirt collection well: 5000 CN Chrome-nickel steel (V2A)
		emco dirt collection well: 5000 AL+ Aluminium
		emco dirt collection well: 5000 CN+ Chrome-nickel steel (V2A)
Tread surface	The weatherproof Outdoor insert for thorough, effective removal of coarse dirt. Combined with stainless steel tiles for optimum orientation in the entrance area the blind or visually impaired (to DIN 32984).	emco special frame with substructure: A Version A: with installation frame, rectangular tube profiles, grid support and height adjustment.
		emco special frame with substructure: B Version B: with installation frame, grid support and rectangular tube profiles
Slip resistance	Slip-resistance of the insert: R11, slip- resistance of the stainless steel tiles: R10 (in accordance with DIN 51130)	emco special frame with substructure: C Type C: with installation frame and rectangular tube profiles
Colour fastness to artificial light ISO 105-	excellent 7	Mat joining brackets: MV Supplied as standard with mats in several parts
B02		Rubber underlay 3 mm: GU 3
Colour fastness to rubbing ISO 105 X12	good 4-5	Rubber underlay 5 mm: GU 5 Rubber underlay 1 mm: GU 1
Colour fastness to water ISO 105 E01	good 4-5	



Suitable for:	Clinic/Hospital
Retirement homes and Care-/Nursery Homes	Warehouse
Arena	Apartment building
medical practice	Trade fair
Train station	School
DIY store	Sports hall
Offices and administrative buildings	Supermarket
Family home	
Shopping centre	Service and services
Retail sector	Construction site advice
University / Higher education institution	Dimensioning
airport	Measured using laser measuring device on site.
Hotel	Installation service
Industry	Fitting and installation service
Kindergarten/Nursery	Repairs



Colours



Anthracite



Brown



Red

Warranty conditions are available at: www.emco-bau.com/en/warranty-conditions/

Subject to technical modifications

emco Bautechnik GmbH · Breslauer Straße 34 · 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com

