



The tactile guidance system for the very highest standards in design and functionality.



Indoor and outdoor (covered, Zone 1+2)

Description

Roll-up, hard-wearing entrance mat for supported or self-supporting laying. Fitted with small (122 mm) or large (300 mm) stainless steel tiles for tactile guidance. Each tile occupies three aluminium profile bars. Mat is produced to fit width perfectly; depth obtained using spacing increments of 100 mm. Option of dimpled tiles for attention panel.



Indoor and Street dust, outdoor (cohair, sand, ash vered, Zone textile fibres, 1+2) small leaves and twins, etc.

Street dust,The emcohair, sand, ash,entrance mattextile fibres,as a guidancesmall leavessystem forand twigs, etc.the visuallyimpaired

R 11 slip resis- 4 year war-

ranty

tance as per

DIN 51130



Roll-over and drive-over capability:	Wheelchairs	Accessories
	Prams	emco installation frame 500: 500-25 AL Aluminium
	hand trolleys	emco installation frame 500: 500-25 CN Chrome-nickel steel (V2A)
	Light shopping trolleys	emco LUMINA: LUMINA + LED Aluminium
	Sack-/hand truck	emco cover strip: C22 Chrome-nickel steel (V2A)
		emco dirt collection well: 5000 AL Aluminium
	pallet trucks Electric lift truck Cars	emco dirt collection well: 5000 CN Chrome-nickel steel (V2A)
		emco dirt collection well: 5000 AL+ Aluminium
		emco dirt collection well: 5000 CN+ Chrome-nickel steel (V2A)
Standard profile clearance approx. (mm)	5 mm, rubber spacers	emco dirt collection well: 5022 AL Aluminium
Connection	Plastic-coated steel cable	emco dirt collection well: 5022 CN Chrome-nickel steel (V2A)
Max. width/profile length for individual section (mm):	1200	emco dirt collection well: 5022 AL+ Aluminium
		emco dirt collection well: 5022 CN+ Chrome-nickel steel (V2A)
Profile width (mm)	28.65	emco dirt collection well: 5022 AL Aluminium
Depth/walking depth	800	emco dirt collection well: 5022 CN Chrome-nickel steel (V2A)
for individual section (mm):		emco dirt collection well: 5022 AL+ Aluminium
().	Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside Recessed, robust, weather-proof coarse-fibre ribbed carpet strips (brand-name fibres) for even better dirt removal. Combined with stainless steel tiles for optimum way guidance for the blind in the entrance area.	emco dirt collection well: 5022 CN+ Chrome-nickel steel (V2A)
Support chassis		emco dirt collection well: 5000 AL Aluminium
		emco dirt collection well: 5000 CN Chrome-nickel steel (V2A)
Tread surface		emco dirt collection well: 5000 AL+ Aluminium
		emco dirt collection well: 5000 CN+ Chrome-nickel steel (V2A)
		emco special frame with substructure: A Version A: with installation frame, rectangular tube profiles, grid support and height adjustment.
Slip resistance	Slip-resistance of the insert: R11, slip- resistance of the stainless steel tiles: R10 (in accordance with DIN 51130)	emco special frame with substructure: B Version B: with installation frame, grid support and rectangular tube profiles
Colour fastness to artificial light ISO 105- B02	good 6	emco special frame with substructure: C Type C: with installation frame and rectangular tube profiles
Colour fastness to		Mat joining brackets: MV Supplied as standard with mats in several parts
rubbing ISO 105 X12	good 4	Rubber underlay 3 mm: GU 3
Colour fastness to water ISO 105 E01	good 5	Rubber underlay 5 mm: GU 5
		Rubber underlay 1 mm: GU 1



Suitable for:	Kindergarten/Nursery
Retirement homes and Care-/Nursery Homes	Clinic/Hospital
Arena	Warehouse
medical practice	Apartment building
Train station	Trade fair
DIY store	School
Offices and administrative buildings	Sports hall
Family home	Supermarket
Shopping centre	
Retail sector	Service and services
University / Higher education institution	Construction site advice
airport	Dimensioning
Hotel	Measured using laser measuring device on site.
Industry	Installation service
	Fitting and installation service



Colours



Anthracite no. 200

Warranty conditions are available at: www.emco-bau.com/en/warranty-conditions/

Subject to technical modifications

emco Bautechnik GmbH · Breslauer Straße 34 · 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com

