

emco Bau

emco DIPLOMAT Premium SPIN®Safe With MAXIMUS insert 22 SPIN /P Maximus

Model	22 SPIN/P Maximus
Load	Normal to heavy
Support chassis	Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside
Approx. height (mm)	25.9
Tread surface	The stylish Maximus insert is made from high-quality tufted velour and is characterised by an exclusive appearance. Used with stainless steel tiles for optimum orientation in the entrance area for the blind or those visually impaired (to DIN 32984).
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Slip resistance	Slip-resistance of the insert: R12, slip-resistance of the stainless steel tiles: R9 (in accordance with DIN 51130)
Colours	Anthracite 80.02 Brown 80.04 Red 80.07 Black mottled 81.01 Black 80.01
Connection	Plastic-coated steel cable
Warranty	5 years guarantee Warranty conditions are available at:
Colour fastness to artificial light ISO 105-B02	good 5-6
Colour fastness to rubbing ISO 105 X12	good 5
Colour fastness to water ISO 105 E01	good 5
Dimensions	Mat width:.....mm (bar length) Mat depth:.....mm (walking direction)
Contact	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com