

## emco Bau

## emco DIPLOMAT Premium SPIN®Safe With MAXIMUS insert 22 SPIN /P Maximus

Model 22 SPIN/P Maximus

Load Normal to heavy

Support chassis Reinforced support chassis made using rigid aluminium with

sound absorbing insulation on the underside

25.9 Approx. height (mm)

**Tread surface** The stylish Maximus insert is made from high-quality tufted

> velour and is characterised by an exclusive appearance. Used with stainless steel tiles for optimum orientation in the entrance area for the blind or those visually impaired (to DIN

32984).

Standard profile clearance approx.

(mm)

5 mm, rubber spacers

Slip resistance Slip-resistance of the insert: R12, slip-resistance of the

stainless steel tiles: R9 (in accordance with DIN 51130)

Colours Anthracite 80.02

> Brown 80.04 Red 80.07

Black mottled 81.01

Black 80.01

Connection Plastic-coated steel cable

Warranty 5 years guarantee

Warranty conditions are available at:

Colour fastness to artificial light ISO

105-B02

good 5-6

Colour fastness to rubbing ISO 105

X12

good 5

Colour fastness to water ISO 105 E01 good 5

**Dimensions** Mat width:....mm (bar length)

Mat depth:....mm (walking direction)

Contact emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-

> 49808 Lingen (Ems) Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 Email: bau@emco.de ·

www.emco-bau.com