

## emco Bau

### emco DIPLOMAT Original Large With ribbed carpet insert 512 LR

|   |   |
|---|---|
| Model   | 512 LR  |
| Load  | Normal  |
| Support chassis   | Made using rigid aluminium with sound absorbing insulation on the underside   |
| Support chassis colour  | Aluminium as standard. Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel  |
| Approx. height (mm)   | 12  |
| Tread surface   | Recessed, robust, weather-proof, ribbed carpet strips.  |
| Standard profile clearance approx. (mm)                       | 5 mm, rubber spacers  |
| Automatic door systems  | Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005   |
| Slip resistance   | R 11 slip resistance as per DIN 51130   |
| Colours   | Anthracite no. 200<br>Brown no. 485<br>Light grey no. 220<br>Red no. 305<br>Sand no. 430  |
| Flammability  | Insert for Light Grey and Anthracite ribbed carpet colours available on request (surcharge applicable) with fire classification Cfl-s1 according to EN 13501.   |
| Connection  | Plastic-coated stainless steel cable  |
| Warranty  | 4 year warranty<br>Warranty conditions are available at:  |
| Insert certified to TÜV PROFICERT-product interior (Standard) | French VOC regulation<br>LEED v4 (outside North America)<br>BREEAM Exemplary Level<br>Belgian VOC regulation<br>AgBB (Committee for Health-related Evaluation of Building Products)<br>MVV TB Appendix 8, 9 / ABG |
| Pile material   | 100% PP (polypropylene)   |
| Colour fastness to artificial light ISO 105-B02               | good 6  |

**Colour fastness to rubbing ISO 105 X12**      good 4

**Colour fastness to water ISO 105 E01**      good 5

**Dimensions**

Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)

**Contact**

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: [bau@emco.de](mailto:bau@emco.de) · [www.emco-bau.com](http://www.emco-bau.com)