

emco Bau

emco DIPLOMAT Premium Large With Conform insert and scraping edge 512 PL Conform K

| | |
|--|---|
| Model | 512 PL Conform K |
| Load | Normal |
| Support chassis | Made using rigid aluminium with Premium sound absorbing insulation on the underside |
| Support chassis colour | Aluminium as standard. Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel |
| Approx. height (mm) | 12 |
| Tread surface | The Conform insert made of recycled materials is the perfect complement to wooden surroundings and can be used in a whole host of environments. The additional profile increases the cleaning power. |
| Standard profile clearance approx. (mm) | 5 mm, rubber spacers |
| Automatic door systems | Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 |
| Colours | 76.01 Anthracite 76.02 Beige 76.04 Brown |
| Special colours | Other colours from our clean-off collection also available. |
| Flammability | Insert with fire classification Cfl-s1 according to EN 13501. |
| Connection | Plastic-coated stainless steel cable |
| Warranty | 5 years guarantee Warranty conditions are available at: |
| Insert certified to TÜV PROFiCERT-product interior (Standard) | French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG |
| Pile material | 100% PA 6 (polyamide) |
| Use classification EN1307 | class 33 (heavy commercial use) |
| Dimensions | Mat width:.....mm (bar length) |



Contact

Mat depth:.....mm (walking direction)

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-
49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-
500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·
www.emco-bau.com