

emco Bau

emco DIPLOMAT Premium Large With MAXIMUS insert 512 PL Maximus

Model	512 PL Maximus
Load	Normal
Support chassis	Made using rigid aluminium with sound absorbing insulation on the underside
Support chassis colour	Standard natural anodized Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
Approx. height (mm)	12
Note on height	The insert can actually be approx. 2-3 mm higher due to the wear layer.
Tread surface	The stylish Maximus insert stands out from the crowd with its premium-quality tufted velour and high-end design.
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile gaps, for revolving doors, available in 3mm according to DIN EN 16005
Slip resistance	R 12 slip resistance as per DIN 51130
Colours	Anthracite 80.02 Brown 80.04 Red 80.07 Black mottled 81.01 Black 80.01
Special colours	Other colours from our clean-off collection also available.
Flammability	Fire classification for the complete mat system Bfl-s1 in accordance with EN 13501
Connection	Plastic-coated stainless steel cable
Warranty	5 years guarantee Warranty conditions are available at:
Insert certified to TÜV PROFiCERT-product interior (Standard)	French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products)

MVV TB Appendix 8, 9 / ABG

Pile material

100% PA 6.6 (polyamide)

Use classification EN1307

Property suitable inlay 33

Colour fastness to artificial light ISO 105-B02

good 5-6

Colour fastness to rubbing ISO 105 X12

good 5

Colour fastness to water ISO 105 E01

good 5

Bacterial reduction EHEC ASTM-e2149

29,4 %

Bacterial reduction staphylococcus aureus ASTM-e2149

16,7 %

Bacterial reduction klebsiella pneumoniae ASTM-e2149

68,2 %

Dimensions

Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)

Contact

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 Email: bau@emco.de · www.emco-bau.com