

emco Bau

emco DIPLOMAT Premium Large With Maximus insert and scraping edge 512 PL Maximus K

Model 512 PL Maximus K

Load Normal

Support chassis Made using rigid aluminium with sound absorbing insulation

on the underside

Support chassis colour Standard natural anodized Anodised colours for an

additional charge: EV3 gold, C33 mid-bronze, C35 black or

C31 stainless steel

Approx. height (mm) 12

Tread surface The stylish Maximus insert stands out from the crowd with

its premium-quality tufted velour and high-end design. The

additional profile increases the cleaning power.

Standard profile clearance approx.

(mm)

5 mm, rubber spacers

Automatic door systems Profile gaps, for revolving doors, available in 3mm

according to DIN EN 16005

Colours Anthracite 80.02

Brown 80.04 Red 80.07

Black mottled 81.01

Black 80.01

Special colours Other colours from our clean-off collection also available.

Flammability Insert with fire classification Bfl-s1 according to EN 13501.

Connection Plastic-coated stainless steel cable

Warranty 5 years guarantee

Warranty conditions are available at:

Insert certified to TÜV PROFICERT-

product interior (Standard)

French VOC regulation

LEED v4 (outside North America)

BREEAM Exemplary Level Belgian VOC regulation

AgBB (Committee for Health-related Evaluation of Building

Products)

MVV TB Appendix 8, 9 / ABG

Pile material 100% PA 6.6 (polyamide)

Use classification EN1307 Property suitable inlay 33



Dimensions Mat width:....mm (bar length)

Mat depth:....mm (walking direction)

Contact emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-

49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·

www.emco-bau.com