

emco Bau

emco MARSCHALL Premium Large With Conform insert 512 PSL Conform

Model 512 PSL Conform

Load Normal to heavy

Support chassis Reinforced support chassis made using rigid aluminium with

sound absorbing insulation on the underside

Support chassis colour Standard natural anodized Anodised colours for an

additional charge: EV3 gold, C33 mid-bronze, C35 black or

C31 stainless steel

Approx. height (mm) 12

Note on height The insert can actually be approx. 2 mm higher due to the

wear layer.

Tread surface The Conform insert made of recycled materials is the

perfect complement to wooden surroundings and can be

used in a whole host of environments.

Standard profile clearance approx.

(mm)

5 mm, rubber spacers

Automatic door systems Profile gaps, for revolving doors, available in 3mm

according to DIN EN 16005

Slip resistance R 12 slip resistance as per DIN 51130

Colours Anthracite 76.01

Beige 76.02 Brown 76.04

Special colours Other colours from our clean-off collection also available.

Flammability Fire classification for the complete mat system Cfl-s1 in

accordance with EN 13501

Connection Plastic-coated stainless steel cable

Warranty 5 years guarantee

Warranty conditions are available at:

Insert certified to TÜV PROFICERT-

product interior (Standard)

French VOC regulation

LEED v4 (outside North America)

BREEAM Exemplary Level Belgian VOC regulation

AgBB (Committee for Health-related Evaluation of Building

Products)

MVV TB Appendix 8, 9 / ABG



Pile material 100% PA 6 (polyamide)

Use classification EN1307 Property suitable inlay 33

Bacterial reduction EHEC ASTM-e2149 16,1 %

Bacterial reduction staphylococcus

aureus ASTM-e2149

0,0 %

Bacterial reduction klebsiella

pneumoniae ASTM-e2149

65,6 %

Dimensions Mat width:....mm (bar length)

Mat depth:....mm (walking direction)

Contact emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-

49808 Lingen (Ems) Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 Email: bau@emco.de ·

www.emco-bau.com