
### **Model 512 PSL Conform K**



The extra-wide Premium entrance mat with the Conform insert made of regenerated materials perfectly matches wood in colour and can be used in a wide variety of ways. Particularly suitable for collecting fine dirt. The additional profile provides an extra cleaning effect. Ideal for buildings with normal to heavy loads.







Indoor and outdoor (covered, Zone 1+2)

#### Description

Rollable, extremely hard-wearing, premium entrance mat with extrawide profile bars and performance insert for supported installation options. Customisable widths and walking depths available without a compensation profile. Available in any geometric shape.



Indoor and outdoor (covered, Zone 1+2)



Street dust, hair, sand, ash, textile fibres, small leaves and twigs, etc.



Damp street dust, damp sand deposits, dust, etc.



5 years guarantee



Cfl-s1



class 32 (general commercial use)



## **Model 512 PSL Conform K**

Approx. height (mm)	12
Roll-over and drive-over capability:	Prams Sack-/hand truck Wheelchairs
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005
Connection	Plastic-coated stainless steel cable
Max. width/profile length for individual section (mm):	3000
Profile width (mm)	46.5
Weight (kg/m²)	10,5
Mat division as per factory standards	From a profile length of 3000 mm or a maximum mat weight of 25 kg. For profile lengths above 2300 mm, a surcharge is applicable . Mat devisions/ splits possible at customer's request.
Support chassis	Reinforced support chassis made using rigid aluminium with Premium sound absorbing insulation on the underside
Support chassis colour	Aluminium as standard. Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
Tread surface	The Conform insert made of recycled materials is the perfect complement to wooden surroundings and can be used in a whole host of environments. The additional profile increases the cleaning power.
Flammability	Insert with fire classification Cfl-s1 according to EN 13501.
Pile material	100% PA 6 (polyamide)
Use classification EN1307	class 33 (heavy commercial use)

Accessories	
emco installation frame 500: 500-15 AL Aluminium	
emco installation frame 500: 500-15 CN Chrome-nickel steel (V2A)	
emco ramp edge: A12 Aluminium	
emco cover strip: C12 Chrome-nickel steel (V2A)	
emco INOX®: LINEO 12 Chrome-nickel steel (V2A)	
emco dirt collection well: 5512AL Aluminium	
emco dirt collection well: 5512CN Chrome-nickel steel (V2A)	
emco dirt collection well: 5512AL Aluminium	
emco dirt collection well: 5512CN Chrome-nickel steel (V2A)	
Rubber underlay 3 mm: GU 3	
Rubber underlay 5 mm: GU 5	
Rubber underlay 1 mm: GU 1	
Mat joining brackets: MV Supplied as standard with mats in several parts	

Suitable for:		
Retirement homes and Care-/Nursery Homes		
medical practice		
Offices and administrative buildings		
Family home		
Retail sector		
Hotel		
Kindergarten/Nursery		
Apartment building		
School		
Sports hall		

Insert certified to TÜV PROFICERT- product interior (Standard)	
French VOC regulation	
LEED v4 (outside North America)	
BREEAM Exemplary Level	
Belgian VOC regulation	
AgBB (Committee for Health-related Evaluation of Building Products)	
MVV TB Appendix 8, 9 / ABG	



# emco MARSCHALL Premium Large With Conform insert and scraping edge

# **Model 512 PSL Conform K**

Service and services	Installation service
Construction site advice	Fitting and installation service
Dimensioning	Repairs
Measured using laser measuring device on site.	The product can be disposed of or recycled in an environmentally friendly way.



# emco MARSCHALL Premium Large With Conform insert and scraping edge

## **Model 512 PSL Conform K**


### Colours



76.01 Anthracite



76.02 Beige



76.04 Brown

Warranty conditions are available at: www.emco-bau.com/en/warranty-conditions/



