

emco Bau

emco MARSCHALL Premium Large With Innova insert and scraping edge 512 PSL Innova K

Model 512 PSL Innova K
Load Normal to heavy

Support chassis Reinforced support chassis made using rigid aluminium with

sound absorbing insulation on the underside

Support chassis colour Standard natural anodized Anodised colours for an

additional charge: EV3 gold, C33 mid-bronze, C35 black or

C31 stainless steel

Approx. height (mm) 12

Tread surface The exceptionally flexible Innova insert not only creates a

sophisticated impression but also improves room acoustics.

The additional profile increases the cleaning power.

Standard profile clearance approx.

(mm)

5 mm, rubber spacers

Automatic door systems Profile gaps, for revolving doors, available in 3mm

according to DIN EN 16005

Colours 36.01 black

36.02 anthracite

36.03 grey

Special colours

Other colours from our clean-off collection also available.

Flammability

Insert with fire classification Cfl-s1 according to EN 13501.

Connection Plastic-coated stainless steel cable

Warranty 5 years guarantee

Warranty conditions are available at:

Insert certified to TÜV PROFICERT-

product interior (Standard)

French VOC regulation

LEED v4 (outside North America)

BREEAM Exemplary Level Belgian VOC regulation

AgBB (Committee for Health-related Evaluation of Building

Products)

MVV TB Appendix 8, 9 / ABG

Pile material 100% PA 6 (polyamide)
Use classification EN1307 Property suitable inlay 33

Dimensions Mat width:....mm (bar length)

Mat depth:....mm (walking direction)



Contact

emco Bautechnik GmbH · Breslauer Straße 34 · 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com