

emco Bau

emco MARSCHALL Premium Large With Maximus Image insert and scraping edge 512 PSL Maximus Image K

Model	512 PSL Maximus Image K
Load	Normal to heavy
Support chassis	Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside
Support chassis colour	Standard natural anodized Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
Approx. height (mm)	12
Tread surface	Embedded, robust MAXIMUS inserts in Bfl-S1 quality (clean-off floor covering made from special polyamide yarn, 100%)
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile gaps, for revolving doors, available in 3mm according to DIN EN 16005
Colours	I350 Blue grey I80 Bordeaux I260 Brown I380 Dark grey I210 Dark green I120 Lilac I30 Yellow/orange I20 Yellow I420 Gold I270 Graphite I340 Grey beige I370 Grey I250 Green I170 Light blue I360 Light grey I440 Light green I90 Light red I100 Cherry I430 Salmon pink I230 Leaf green I290 Light blue

I110 Purple
 I140 Magenta
 I200 Marine blue
 I330 Chestnut
 I220 Mint
 I40 Orange
 I70 Oxide red
 I180 Petrol blue
 I150 Peach
 I310 Fawn brown
 I60 Red
 I160 Royal blue
 I320 Sand
 I240 Reed green
 I390 Black
 I300 Silver
 I190 Emerald green
 I280 Steel blue
 I410 Steel grey
 I450 Sunset
 I50 Terracotta
 I130 Grape
 I400 White*
 I10 Lemon

Special colours

Other colours from our clean-off collection also available.

Flammability

Insert with fire classification Bfl-s1 according to EN 13501.

Connection

Plastic-coated stainless steel cable

Warranty

5 years guarantee

Warranty conditions are available at:

**Insert certified to TÜV PROFiCERT-
product interior (Standard)**

French VOC regulation

LEED v4 (outside North America)

BREEAM Exemplary Level

Belgian VOC regulation

AgBB (Committee for Health-related Evaluation of Building Products)

MVV TB Appendix 8, 9 / ABG

Pile material

100% PA 6.6 (polyamide)

Use classification EN1307

Property suitable inlay 33

Dimensions

Mat width:.....mm (bar length)

Contact

Mat depth:.....mm (walking direction)

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-
49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-
500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·
www.emco-bau.com