

emco Bau

emco MARSCHALL Premium With Maximus insert and scraping edge 512 PS Maximus K

Model	512 PS Maximus K
Load	Normal to heavy
Support chassis	Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside
Support chassis colour	Standard natural anodized Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
Approx. height (mm)	12
Tread surface	Embedded, robust MAXIMUS inserts in Bfl-S1 quality (clean-off floor covering made from special polyamide yarn, 100%)
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile gaps, for revolving doors, available in 3mm according to DIN EN 16005
Colours	Anthracite 80.02 Brown 80.04 Red 80.07 Black mottled 81.01 Black 80.01
Special colours	Other colours from our clean-off collection also available.
Flammability	Insert with fire classification Bfl-s1 according to EN 13501.
Connection	Plastic-coated stainless steel cable
Warranty	5 years guarantee Warranty conditions are available at:
Insert certified to TÜV PROFiCERT-product interior (Standard)	French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG
Pile material	100% PA 6.6 (polyamide)
Use classification EN1307	Property suitable inlay 33
Dimensions	Mat width:.....mm (bar length)

Contact

Mat depth:.....mm (walking direction)

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-
49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-
500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·
www.emco-bau.com