

emco Bau

emco MARSCHALL Original Large With ribbed carpet insert and scraper bar 512 SLRK

| | |
|--|---|
| Model | 512 SLRK |
| Load | Normal to heavy |
| Support chassis | Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside |
| Support chassis colour | Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel |
| Approx. height (mm) | 12 |
| Tread surface | Recessed, robust, weather-proof, ribbed carpet strips, also with scraper bars mounted between the profiles. |
| Standard profile clearance approx. (mm) | 5 mm, rubber spacers |
| Revolving door drives | Our mats with a profile spacing of 3mm in accordance with DIN EN 16005 are available for revolving door drives. |
| Colours | Light grey no. 220 Anthracite no. 200 Red no. 305 Brown no. 485 Sand no. 430 |
| Flammability | Insert available on request (surcharge applicable) with fire classification Cfl-s1 according to EN 13501. |
| Connection | Plastic-coated steel cable |
| Warranty | 4 year warranty Warranty conditions are available at: |
| Insert certified to TÜV PROFiCERT-product interior (Standard) | French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG |
| Pile material | 100% PP (polypropylene) |
| Colour fastness to artificial light ISO 105-B02 | good 6 |
| Colour fastness to rubbing ISO 105 | |

| | |
|---|---|
| X12 | good 4 |
| Colour fastness to water ISO 105 E01 | good 5 |
| Dimensions | Mat width:.....mm (bar length) Mat depth:.....mm (walking direction) |
| BIM Data | BIM Data is available to download from https://www.emco-bau.com/pim/bim-daten-GER.zip . |
| Contact | emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 Email: bau@emco.de · www.emco-bau.com |