Model 512 SLRK





The extra-wide original entrance mat with the successful coarse-fibre ribbed insert is extremely abrasion-resistant and provides maximum dimensional stability. Particularly suitable for collecting fine dirt. The additional profile provides an extra cleaning effect. Ideal for buildings with normal to heavy loads.







Indoor and outdoor (covered, Zone 1+2)

Description

Rollable, extremely hard-wearing, original entrance mat with extrawide profile bars and standard insert for supported installation options. Customisable widths and walking depths available without a compensation profile. Available in any geometric shape.









Street dust, hair, sand, ash, textile fibres, small leaves and twigs, etc.





ranty





Model 512 SLRK

Approx. height (mm)	12
Roll-over and drive-over capability:	Prams
	Sack-/hand truck
	Wheelchairs
Standard profile	
clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile gaps, for revolving doors, available in 3mm according to DIN EN
	16005
Connection	Plastic-coated steel cable
Max. width/profile length for individual section (mm):	3000
Profile width (mm)	46.5
Weight (kg/m²)	9.5
Mat division as per factory standards	From a profile length of 3000 mm or a maximum mat weight of 25 kg. For profile lengths above 2300 mm, a surcharge is applicable . Mat devisions/ splits possible at customer's request.
Support chassis	Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside
Support chassis colour	Standard natural anodized Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
Tread surface	Recessed, robust, weather-proof, ribbed carpet strips, also with scraper bars mounted between the profiles.
Flammability	Insert available on request (surcharge applicable) with fire classification Cfl-s1 according to EN 13501.
Pile material	100% PP (polypropylene)
Colour fastness to artificial light ISO 105- B02	good 6
Colour fastness to rubbing ISO 105 X12	good 4
Colour fastness to water ISO 105 E01	good 5

Accessories	
emco installation frame 500: 500-15 AL Aluminium	
emco installation frame 500: 500-15 CN Chrome-nickel steel (V2A)	
emco ramp edge: A12 Aluminium	
emco cover strip: C12 Chrome-nickel steel (V2A)	
emco INOX®: LINEO 12 Chrome-nickel steel (V2A)	
emco dirt collection well: 5512AL Aluminium	
emco dirt collection well: 5512CN Chrome-nickel steel (V2A)	
Rubber underlay 1 mm: GU 1	
Rubber underlay 3 mm: GU 3	
Rubber underlay 5 mm: GU 5	
Mat joining brackets: MV Supplied as standard with mats in several parts	

Suitable for:	
Retirement homes and Care-/Nursery Homes	
medical practice	
Offices and administrative buildings	
Family home	
Retail sector	
Hotel	
Kindergarten/Nursery	
Apartment building	
School	
Sports hall	

Insert certified to TÜV PROFICERT- product interior (Standard)	
French VOC regulation	
LEED v4 (outside North America)	
BREEAM Exemplary Level	
Belgian VOC regulation	
AgBB (Committee for Health-related Evaluation of Building Products)	
MVV TB Appendix 8, 9 / ABG	



emco MARSCHALL Original Large With ribbed carpet insert and scraper bar

Model 512 SLRK

Service and services	Installation service
Construction site advice	Fitting and installation service
Dimensioning	Repairs
Measured using laser measuring device on site.	The product can be disposed of or recycled in an environmentally friendly way.



Model 512 SLRK

Colours



Light grey no. 220



Red no. 305



Warranty conditions are available at: www.emco-bau.com/en/warranty-conditions/

Subject to technical modifications



Anthracite no. 200



