

## emco Bau

### emco DIPLOMAT Original With rubber insert and brush strip 517 GB

<b>Model</b>	517 GB
<b>Load</b>	Normal to heavy
<b>Support chassis</b>	Made using aluminium with sound absorbing insulation on the underside
<b>Support chassis colour</b>	Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
<b>Approx. height (mm)</b>	17
<b>Tread surface</b>	Recessed, robust, weather-proof profiled rubber inserts.
<b>Standard profile clearance approx. (mm)</b>	5 mm, rubber spacers
<b>Revolving door drives</b>	Our mats with a profile spacing of 3mm in accordance with DIN EN 16005 are available for revolving door drives.
<b>Colours</b>	black grey Black
<b>Flammability</b>	Insert with fire classification Bfl-s1 according to EN 13501 upon request (for an additional charge, the rubber insert was inspected in complete mat system).
<b>Connection</b>	Thanks to plastic-coated steel cable
<b>Warranty</b>	4 year warranty Warranty conditions are available at:
<b>Dimensions</b>	Mat width:.....mm (bar length) Mat depth:.....mm (walking direction)
<b>BIM Data</b>	BIM Data is available to download from <a href="https://www.emco-bau.com/pim/bim-daten-GER.zip">https://www.emco-bau.com/pim/bim-daten-GER.zip</a> .
<b>Contact</b>	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 Email: <a href="mailto:bau@emco.de">bau@emco.de</a> · <a href="http://www.emco-bau.com">www.emco-bau.com</a>