

## **Model 517 LRK**





The extra-wide original entrance mat with the effective, coarse-fibre rib insert is exceptionally abrasion resistant and offers maximum dimensional stability. Particularly ideal for collecting fine dirt. The additional profile offers even more cleaning power. Optimally designed for buildings exposed to average to heavy footfall.







Indoor and outdoor (covered, Zone 1+2)

#### Description

Rollable and hard-wearing original entrance mat with extra-wide profile bars and standard insert for supported installation options. Customisable widths and walking depths available without a compensation profile. Available in any geometric shape.









Indoor and outdoor (covered, Zone

Street dust, hair, sand, ash, ranty textile fibres, small leaves and twigs, etc.

4 year war-





# **Model 517 LRK**

Approx. height (mm)	17
Roll-over and drive-over capability:	Prams Sack-/hand truck
	Wheelchairs
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005
Connection	Plastic-coated steel cable
Max. width/profile length for individual section (mm):	3000
Profile width (mm)	44
Depth/walking depth for individual section (mm):	1500
Weight (kg/m²)	9.4
Mat division as per factory standards	From a profile length of 3000 mm or a maximum mat weight of 30 kg. For profile lengths above 2300 mm, a surcharge is applicable . Mat devisions/ splits possible at customer's request.
Support chassis	Made using rigid aluminium with sound absorbing insulation on the underside
Support chassis colour	Aluminium as standard. Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
Tread surface	Recessed, robust, weather-proof, ribbed carpet strips, also with scraper bars mounted between the profiles.
Flammability	Insert for Light Grey and Anthracite ribbed carpet colours available on request (surcharge applicable) with fire classification Cfl-s1 according to EN 13501.
Pile material	100% PP (polypropylene)
Colour fastness to artificial light ISO 105- B02	good 6
Colour fastness to rubbing ISO 105 X12	good 4
Colour fastness to water ISO 105 E01	good 5

Accessories	
emco installation frame 500: 500-20 AL Aluminium	
emco installation frame 500: 500-20 CN Chrome-nickel steel (V2A)	
emco ramp edge: A17 Aluminium	
emco T-profile: T17	
emco cover strip: C17 Chrome-nickel steel (V2A)	
emco INOX®: LINEO 17 Chrome-nickel steel (V2A)	
emco INOX®: QUADRO 17 Chrome-nickel steel (V2A)	
emco dirt collection well: 5517AL Aluminium	
emco dirt collection well: 5517CN Chrome-nickel steel (V2A)	
emco dirt collection well: 5517AL Aluminium	
emco dirt collection well: 5517CN Chrome-nickel steel (V2A)	
Rubber underlay 3 mm: GU 3	
Rubber underlay 5 mm: GU 5	
Rubber underlay 1 mm: GU 1	
Mat joining brackets: MV Supplied as standard with mats in several parts	

Suitable for:
Retirement homes and Care-/Nursery Homes
medical practice
Offices and administrative buildings
Family home
Retail sector
Hotel
Kindergarten/Nursery
Apartment building
School
Sports hall

Insert certified to TÜV PROFICERT- product interior (Standard)	
French VOC regulation	
LEED v4 (outside North America)	
BREEAM Exemplary Level	
Belgian VOC regulation	
AgBB (Committee for Health-related Evaluation of Building Products)	
MVV TB Appendix 8, 9 / ABG	



# emco DIPLOMAT Original Large With ribbed carpet insert and scraper bar

# **Model 517 LRK**

Service and services	Installation service
Construction site advice	Fitting and installation service
Dimensioning	Repairs
Measured using laser measuring device on site.	The product can be disposed of or recycled in an environmentally friendly way.



### emco DIPLOMAT Original Large With ribbed carpet insert and scraper bar

## **Model 517 LRK**

#### Colours



Light grey no. 220



Red no. 305



Warranty conditions are available at: www.emco-bau.com/en/warranty-conditions/

Subject to technical modifications



Anthracite no. 200



