

emco Bau

emco DIPLOMAT Premium Large With Maximus Image insert and scraping edge 517 PL Maximus Image K

Model	517 PL Maximus Image K
Load	Normal to heavy
Support chassis	Made using aluminium with sound absorbing insulation on the underside
Support chassis colour	Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
Approx. height (mm)	17
Tread surface	The Maximus Image insert is suitable for single-colour printing in a personally chosen colour. The additional profile increases the cleaning effect.
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Revolving door drives	Our mats with a profile spacing of 3mm in accordance with DIN EN 16005 are available for revolving door drives.
Special colours	Other colours from our clean-off collection also available.
Flammability	Insert with fire classification Bfl-s1 according to EN 13501.
Connection	Plastic-coated steel cable
Warranty	5 years guarantee Warranty conditions are available at:
Insert certified to TÜV PROFiCERT-product interior (Standard)	French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG
Pile material	100% PA 6.6 (polyamide)
Use classification EN1307	Property suitable inlay 33
Dimensions	Mat width:.....mm (bar length) Mat depth:.....mm (walking direction)
BIM Data	BIM Data is available to download from https://www.emco-bau.com/pim/bim-daten-GER.zip .
Contact	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) Germany · Phone: +49 (0) 591/9140-



500 · Fax: +49 (0) 591/9140-852 Email: bau@emco.de ·
www.emco-bau.com