

emco Bau

emco MARSCHALL Premium Large With Innova insert and scraping edge 517 PSL Innova K

| Model | 517 PSL Innova K |
|---|---|
| Load | Extremely heavy |
| Support chassis | Reinforced support chassis made using rigid aluminium with Premium sound absorbing insulation on the underside |
| Support chassis colour | Aluminium as standard. Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel |
| Approx. height (mm) | 17 |
| Tread surface | The exceptionally flexible Innova insert not only creates a sophisticated impression but also improves room acoustics. The additional profile increases the cleaning power. |
| Standard profile clearance approx. (mm) | 5 mm, rubber spacers |
| Automatic door systems | Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 |
| Colours | 36.01 black |
| | 36.02 anthracite |
| | 36.03 grey |
| Special colours | Other colours from our clean-off collection also available. |
| Flammability | Insert with fire classification Cfl-s1 according to EN 13501. |
| Connection | Plastic-coated stainless steel cable |
| Warranty | 5 years guarantee |
| | Warranty conditions are available at: |
| Insert certified to TÜV PROFiCERT- product interior (Standard) | French VOC regulation |
| | LEED v4 (outside North America) |
| | BREEAM Exemplary Level |
| | Belgian VOC regulation |
| | AgBB (Committee for Health-related Evaluation of Building Products) |
| | MVV TB Appendix 8, 9 / ABG |
| Pile material | 100% PA 6 (polyamide) |
| Use classification EN1307 | class 33 (heavy commercial use) |
| Dimensions | Mat width:mm (bar length) |
| | Mat depth:mm (walking direction) |



emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com