

emco Bau

emco MARSCHALL Premium Large With Maximus Image insert and scraping edge 517 PSL Maximus Image K

Model	517 PSL Maximus Image K
Load	Extremely heavy
Support chassis	Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside
Support chassis colour	Standard natural anodized Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
Approx. height (mm)	17
Tread surface	Embedded, robust MAXIMUS inserts in Bfl-S1 quality (clean-off floor covering made from special polyamide yarn, 100%)
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile gaps, for revolving doors, available in 3mm according to DIN EN 16005
Colours	I350 Blue grey I80 Bordeaux I260 Brown I380 Dark grey I210 Dark green I120 Lilac I30 Yellow/orange I20 Yellow I420 Gold I270 Graphite I340 Grey beige I370 Grey I250 Green I170 Light blue I360 Light grey I440 Light green I90 Light red I100 Cherry I430 Salmon pink I230 Leaf green I290 Light blue

- I110 Purple
- I140 Magenta
- I200 Marine blue
- I330 Chestnut
- I220 Mint
- I40 Orange
- I70 Oxide red
- I180 Petrol blue
- I150 Peach
- I310 Fawn brown
- I60 Red
- I160 Royal blue
- I320 Sand
- I240 Reed green
- I390 Black
- I300 Silver
- I190 Emerald green
- I280 Steel blue
- I410 Steel grey
- I450 Sunset
- I50 Terracotta
- I130 Grape
- I400 White*
- I10 Lemon

Special colours

Other colours from our clean-off collection also available.

Flammability

Insert with fire classification Bfl-s1 according to EN 13501.

Connection

Plastic-coated stainless steel cable

Warranty

5 years guarantee

Warranty conditions are available at:

**Insert certified to TÜV PROFiCERT-
product interior (Standard)**

French VOC regulation

LEED v4 (outside North America)

BREEAM Exemplary Level

Belgian VOC regulation

AgBB (Committee for Health-related Evaluation of Building Products)

MVV TB Appendix 8, 9 / ABG

Pile material

100% PA 6.6 (polyamide)

Use classification EN1307

Property suitable inlay 33

Dimensions

Mat width:.....mm (bar length)

Contact

Mat depth:.....mm (walking direction)

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-
49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-
500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·
www.emco-bau.com