

emco Bau

emco MARSCHALL Premium With Conform insert 517 PS Conform

| | |
|--|---|
| Model | 517 PS Conform |
| Load | Extremely heavy |
| Support chassis | Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside |
| Support chassis colour | Standard natural anodized Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel |
| Approx. height (mm) | 17 |
| Note on height | The insert can actually be approx. 2 mm higher due to the wear layer. |
| Tread surface | The Conform insert made of recycled materials is the perfect complement to wooden surroundings and can be used in a whole host of environments. |
| Standard profile clearance approx. (mm) | 5 mm, rubber spacers |
| Automatic door systems | Profile gaps, for revolving doors, available in 3mm according to DIN EN 16005 |
| Slip resistance | R 12 slip resistance as per DIN 51130 |
| Colours | Anthracite 76.01 Beige 76.02 Brown 76.04 |
| Special colours | Other colours from our clean-off collection also available. |
| Flammability | Fire classification for the complete mat system Cfl-s1 in accordance with EN 13501 |
| Connection | Plastic-coated stainless steel cable |
| Warranty | 5 years guarantee Warranty conditions are available at: |
| Insert certified to TÜV PROFiCERT-product interior (Standard) | French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG |
| Pile material | 100% PA 6 (polyamide) |
| Use classification EN1307 | Property suitable inlay 33 |

Bacterial reduction EHEC ASTM-e2149 16,1 %

Bacterial reduction staphylococcus aureus ASTM-e2149 0,0 %

Bacterial reduction klebsiella pneumoniae ASTM-e2149 65,6 %

Dimensions

Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)

Contact

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com