

emco Bau

emco MARSCHALL Premium With Innova insert and scraping edge 517 PS Innova K

Model 517 PS Innova K
Load Extremely heavy

Support chassis Reinforced support chassis made using rigid aluminium with

Premium sound absorbing insulation on the underside

Support chassis colour Aluminium as standard. Anodised colours for an additional

charge: EV3 gold, C33 mid-bronze, C35 black or C31

stainless steel

Approx. height (mm) 17

Tread surface The exceptionally flexible Innova insert not only creates a

sophisticated impression but also improves room acoustics.

The additional profile increases the cleaning power.

Standard profile clearance approx.

(mm)

5 mm, rubber spacers

Automatic door systems Profile clearance of 3 mm available as an option for

revolving door drives, in accordance with EN 16005

Colours 36.01 black

36.02 anthracite

36.03 grey

Special colours

Other colours from our clean-off collection also available.

Flammability

Insert with fire classification Cfl-s1 according to EN 13501.

Connection Plastic-coated stainless steel cable

Warranty 5 years guarantee

Warranty conditions are available at:

Insert certified to TÜV PROFICERT-

product interior (Standard)

French VOC regulation

LEED v4 (outside North America)

BREEAM Exemplary Level Belgian VOC regulation

AgBB (Committee for Health-related Evaluation of Building

Products)

MVV TB Appendix 8, 9 / ABG

Pile material 100% PA 6 (polyamide)

Use classification EN1307 class 33 (heavy commercial use)

Dimensions Mat width:....mm (bar length)

Mat depth:....mm (walking direction)



Contact

emco Bautechnik GmbH · Breslauer Straße 34 · 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com