

## emco Bau

### emco MARSCHALL Premium With Outdoor insert 517 PS Outdoor

|                                                             |                                                                                                                                 |
|-------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>Model</b>                                                | 517 PS Outdoor                                                                                                                  |
| <b>Load</b>                                                 | Extremely heavy                                                                                                                 |
| <b>Support chassis</b>                                      | Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside                          |
| <b>Support chassis colour</b>                               | Standard natural anodized Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel |
| <b>Approx. height (mm)</b>                                  | 17                                                                                                                              |
| <b>Tread surface</b>                                        | The weather-resistant Outdoor insert for noticeably thorough removal of coarse dirt.                                            |
| <b>Standard profile clearance approx. (mm)</b>              | 5 mm, rubber spacers                                                                                                            |
| <b>Automatic door systems</b>                               | Profile gaps, for revolving doors, available in 3mm according to DIN EN 16005                                                   |
| <b>Slip resistance</b>                                      | R 11 slip resistance as per DIN 51130                                                                                           |
| <b>Colours</b>                                              | Anthracite<br>Brown<br>Red                                                                                                      |
| <b>Flammability</b>                                         | Fire classification for the complete mat system Cfl-s1 in accordance with EN 13501                                              |
| <b>Connection</b>                                           | Plastic-coated stainless steel cable                                                                                            |
| <b>Warranty</b>                                             | 5 years guarantee<br>Warranty conditions are available at:                                                                      |
| <b>Pile material</b>                                        | 100% PA 6 (polyamide)                                                                                                           |
| <b>Use classification EN1307</b>                            | Property suitable inlay 33                                                                                                      |
| <b>Colour fastness to artificial light ISO 105-B02</b>      | excellent 7                                                                                                                     |
| <b>Colour fastness to rubbing ISO 105 X12</b>               | good 4-5                                                                                                                        |
| <b>Colour fastness to water ISO 105 E01</b>                 | good 4-5                                                                                                                        |
| <b>Bacterial reduction EHEC ASTM-e2149</b>                  | 22,4 %                                                                                                                          |
| <b>Bacterial reduction staphylococcus aureus ASTM-e2149</b> | 17,3 %                                                                                                                          |
| <b>Bacterial reduction klebsiella pneumoniae ASTM-e2149</b> | 9,8 %                                                                                                                           |
| <b>Dimensions</b>                                           | Mat width:.....mm (bar length)<br>Mat depth:.....mm (walking direction)                                                         |

## Contact

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-  
49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-  
500 · Fax: +49 (0) 591/9140-852 · Email: [bau@emco.de](mailto:bau@emco.de) ·  
[www.emco-bau.com](http://www.emco-bau.com)