

## emco Bau

### emco DIPLOMAT Premium With Care insert and brush strip 517 P Care B

|                                                        |                                                                                                                                                            |
|--------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Model</b>                                           | 517 P Care B                                                                                                                                               |
| <b>Load</b>                                            | Normal to heavy                                                                                                                                            |
| <b>Support chassis</b>                                 | Made using rigid aluminium with Premium sound absorbing insulation on the underside                                                                        |
| <b>Support chassis colour</b>                          | Aluminium as standard. Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel                               |
| <b>Approx. height (mm)</b>                             | 17                                                                                                                                                         |
| <b>Tread surface</b>                                   | The robust and exceptionally abrasion-resistant Care insert for the effective reduction of fine dirt. The additional profile increases the cleaning power. |
| <b>Standard profile clearance approx. (mm)</b>         | 5 mm, rubber spacers                                                                                                                                       |
| <b>Automatic door systems</b>                          | Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005                                                    |
| <b>Colours</b>                                         | 47.01 anthracite<br>47.02 grey<br>47.03 brown<br>47.04 beige<br>grey<br>Black                                                                              |
| <b>Special colours</b>                                 | Other colours from our clean-off collection also available.                                                                                                |
| <b>Flammability</b>                                    | Insert with fire classification Cfl-s1 according to EN 13501.                                                                                              |
| <b>Connection</b>                                      | Plastic-coated stainless steel cable                                                                                                                       |
| <b>Warranty</b>                                        | 5 years guarantee<br>Warranty conditions are available at:                                                                                                 |
| <b>Pile material</b>                                   | 100% PA 6 (polyamide)                                                                                                                                      |
| <b>Use classification EN1307</b>                       | class 33 (heavy commercial use)                                                                                                                            |
| <b>Colour fastness to artificial light ISO 105-B02</b> | good 5-6                                                                                                                                                   |
| <b>Colour fastness to rubbing ISO 105 X12</b>          | good 4-5                                                                                                                                                   |
| <b>Colour fastness to water ISO 105 E01</b>            | good 4-5                                                                                                                                                   |
| <b>Dimensions</b>                                      | Mat width:.....mm (bar length)<br>Mat depth:.....mm (walking direction)                                                                                    |

## Contact

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-  
49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-  
500 · Fax: +49 (0) 591/9140-852 · Email: [bau@emco.de](mailto:bau@emco.de) ·  
[www.emco-bau.com](http://www.emco-bau.com)