

## emco Bau

### emco DIPLOMAT Premium With Care insert and scraping edge 517 P Care K

|   |   |
|---|---|
| Model   | 517 P Care K  |
| Load  | Normal to heavy   |
| Support chassis   | Made using rigid aluminium with Premium sound absorbing insulation on the underside   |
| Support chassis colour  | Aluminium as standard. Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel  |
| Approx. height (mm)   | 17  |
| Tread surface   | The robust and exceptionally abrasion-resistant Care insert for the effective reduction of fine dirt. The additional profile increases the cleaning power.  |
| Standard profile clearance approx. (mm)                       | 5 mm, rubber spacers  |
| Automatic door systems  | Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005   |
| Colours   | 47.01 anthracite<br>47.02 grey<br>47.03 brown<br>47.04 beige  |
| Special colours   | Other colours from our clean-off collection also available.   |
| Flammability  | Insert with fire classification Cfl-s1 according to EN 13501.   |
| Connection  | Plastic-coated stainless steel cable  |
| Warranty  | 5 years guarantee<br>Warranty conditions are available at:  |
| Insert certified to TÜV PROFiCERT-product interior (Standard) | French VOC regulation<br>LEED v4 (outside North America)<br>BREEAM Exemplary Level<br>Belgian VOC regulation<br>AgBB (Committee for Health-related Evaluation of Building Products)<br>MVV TB Appendix 8, 9 / ABG |
| Pile material   | 100% PA 6 (polyamide)   |
| Use classification EN1307                                     | class 33 (heavy commercial use)   |
| Colour fastness to artificial light ISO                       |   |

|   |  |
|---|--|
| <b>105-B02</b>                                | good 5-6   |
| <b>Colour fastness to rubbing ISO 105 X12</b> | good 4-5   |
| <b>Colour fastness to water ISO 105 E01</b>   | good 4-5   |
| <b>Dimensions</b>                             | Mat width:.....mm (bar length)<br>Mat depth:.....mm (walking direction)  |
| <b>Contact</b>                                | emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · <a href="http://www.emco-bau.com">www.emco-bau.com</a> |