

emco Bau

emco DIPLOMAT Premium With Conform insert 517 P Conform

Model 517 P Conform

Load Normal to heavy

Support chassis Made using rigid aluminium with sound absorbing insulation

on the underside

Support chassis colour Standard natural anodized Anodised colours for an

additional charge: EV3 gold, C33 mid-bronze, C35 black or

C31 stainless steel

Approx. height (mm) 17

Note on height The insert can actually be approx. 2 mm higher due to the

wear layer.

Tread surface The Conform insert made of recycled materials is the

perfect complement to wooden surroundings and can be

used in a whole host of environments.

Standard profile clearance approx.

(mm)

5 mm, rubber spacers

Automatic door systems Profile gaps, for revolving doors, available in 3mm

according to DIN EN 16005

Slip resistance R 12 slip resistance as per DIN 51130

Colours Anthracite 76.01

Beige 76.02 Brown 76.04

Special colours Other colours from our clean-off collection also available.

Flammability Fire classification for the complete mat system Cfl-s1 in

accordance with EN 13501

Connection Plastic-coated stainless steel cable

Warranty 5 years guarantee

Warranty conditions are available at:

Insert certified to TÜV PROFICERT-

product interior (Standard)

French VOC regulation

LEED v4 (outside North America)

BREEAM Exemplary Level Belgian VOC regulation

AgBB (Committee for Health-related Evaluation of Building

Products)

MVV TB Appendix 8, 9 / ABG

Pile material 100% PA 6 (polyamide)

Use classification EN1307 Property suitable inlay 33



Bacterial reduction EHEC ASTM-e2149 16,1 %

Bacterial reduction staphylococcus

aureus ASTM-e2149

0,0 %

Bacterial reduction klebsiella

pneumoniae ASTM-e2149

65,6 %

Dimensions Mat width:....mm (bar length)

Mat depth:....mm (walking direction)

Contact emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-

49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·

www.emco-bau.com