

emco Bau

emco DIPLOMAT Premium With Conform insert and scraping edge 517 P Conform K

Model 517 P Conform K
Load Normal to heavy

Support chassis Made using rigid aluminium with sound absorbing insulation

on the underside

Support chassis colour Standard natural anodized Anodised colours for an

additional charge: EV3 gold, C33 mid-bronze, C35 black or

C31 stainless steel

Approx. height (mm) 17

Tread surface The Conform insert made of recycled materials is the

perfect complement to wooden surroundings and can be used in a whole host of environments. The additional profile

increases the cleaning power.

Standard profile clearance approx.

(mm)

5 mm, rubber spacers

Automatic door systems Profile gaps, for revolving doors, available in 3mm

according to DIN EN 16005

Colours 76.01 Anthracite

76.02 Beige 76.04 Brown

Special colours Other colours from our clean-off collection also available.

Flammability Insert with fire classification Cfl-s1 according to EN 13501.

Connection Plastic-coated stainless steel cable

Warranty 5 years guarantee

Warranty conditions are available at:

Insert certified to TÜV PROFICERT-

product interior (Standard)

French VOC regulation

LEED v4 (outside North America)

BREEAM Exemplary Level Belgian VOC regulation

AgBB (Committee for Health-related Evaluation of Building

Products)

MVV TB Appendix 8, 9 / ABG

Pile material 100% PA 6 (polyamide)

Use classification EN1307 Property suitable inlay 33

Dimensions Mat width:....mm (bar length)



Contact

Mat depth:....mm (walking direction)

emco Bautechnik GmbH · Breslauer Straße 34 · 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com