

emco Bau

emco DIPLOMAT Premium With Outdoor insert and scraping edge 517 P Outdoor K

Model 517 P Outdoor K
Load Normal to heavy

Support chassis Made using rigid aluminium with sound absorbing insulation

on the underside

Support chassis colour Standard natural anodized Anodised colours for an

additional charge: EV3 gold, C33 mid-bronze, C35 black or

C31 stainless steel

Approx. height (mm) 17

Tread surface The weather-resistant Outdoor insert for noticeably

thorough removal of coarse dirt. The additional profile

increases the cleaning power.

Standard profile clearance approx.

(mm)

5 mm, rubber spacers

Automatic door systems Profile gaps, for revolving doors, available in 3mm

according to DIN EN 16005

Colours Anthracite

Brown

Red

Flammability Insert with fire classification Cfl-s1 according to EN 13501.

Connection Plastic-coated stainless steel cable

Warranty 5 years guarantee

Warranty conditions are available at:

Pile material 100% PA 6 (polyamide)
Use classification EN1307 Property suitable inlay 33

Dimensions Mat width:....mm (bar length)

Mat depth:....mm (walking direction)

Contact emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-

49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·

www.emco-bau.com