

## emco Bau

### emco MARSCHALL Original Large With ribbed carpet insert 517 SLR

<b>Model</b>	517 SLR
<b>Load</b>	Extremely heavy
<b>Support chassis</b>	Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside
<b>Support chassis colour</b>	Standard natural anodized Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
<b>Approx. height (mm)</b>	17
<b>Tread surface</b>	Recessed, robust, weather-proof, ribbed carpet strips.
<b>Standard profile clearance approx. (mm)</b>	5 mm, rubber spacers
<b>Automatic door systems</b>	Profile gaps, for revolving doors, available in 3mm according to DIN EN 16005
<b>Slip resistance</b>	R 11 slip resistance as per DIN 51130
<b>Colours</b>	Anthracite no. 200 Brown no. 485 Light grey no. 220 Red no. 305 Sand no. 430
<b>Flammability</b>	Insert available on request (surcharge applicable) with fire classification Cfl-s1 according to EN 13501.
<b>Connection</b>	Plastic-coated stainless steel cable
<b>Warranty</b>	4 year warranty Warranty conditions are available at:
<b>Insert certified to TÜV PROFiCERT-product interior (Standard)</b>	French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG
<b>Pile material</b>	100% PP (polypropylene)
<b>Colour fastness to artificial light ISO 105-B02</b>	good 6
<b>Colour fastness to rubbing ISO 105</b>	

**X12** good 4

**Colour fastness to water ISO 105 E01** good 5

**Dimensions** Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)

**Contact** emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: [bau@emco.de](mailto:bau@emco.de) · [www.emco-bau.com](http://www.emco-bau.com)