

emco Bau

emco MARSCHALL Original With ribbed carpet insert and scraper bar 517 SRK

| | |
|---|---|
| Model | 517 SRK |
| Load | Extremely heavy |
| Support chassis | Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside |
| Support chassis colour | Aluminium as standard. Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel |
| Approx. height (mm) | 17 |
| Tread surface | Recessed, robust, weather-proof, ribbed carpet strips, also with scraper bars mounted between the profiles. |
| Standard profile clearance approx. (mm) | 5 mm, rubber spacers |
| Automatic door systems | Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 |
| Colours | Light grey no. 220 Anthracite no. 200 Red no. 305 Brown no. 485 Sand no. 430 |
| Flammability | Insert available on request (surcharge applicable) with fire classification Cfl-s1 according to EN 13501. |
| Connection | Plastic-coated stainless steel cable |
| Warranty | 4 year warranty Warranty conditions are available at: |
| Insert certified to TÜV PROFiCERT-product interior (Standard) | French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG |
| Pile material | 100% PP (polypropylene) |
| Colour fastness to artificial light ISO 105-B02 | good 6 |

Colour fastness to rubbing ISO 105 X12 good 4

Colour fastness to water ISO 105 E01 good 5

Dimensions

Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)

Contact

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com