

## emco Bau

## emco DIPLOMAT Premium Large With Care insert and scraping edge 522 PL Care K

Model 522 PL Care K
Load Normal to heavy

Support chassis Made using rigid aluminium with Premium sound absorbing

insulation on the underside

Support chassis colour Aluminium as standard. Anodised colours for an additional

charge: EV3 gold, C33 mid-bronze, C35 black or C31

stainless steel

Approx. height (mm) 22

Tread surface The robust and exceptionally abrasion-resistant Care insert

for the effective reduction of fine dirt. The additional profile

increases the cleaning power.

Standard profile clearance approx.

(mm)

5 mm, rubber spacers

Automatic door systems Profile clearance of 3 mm available as an option for

revolving door drives, in accordance with EN 16005

Colours 47.01 anthracite

47.02 grey 47.03 brown 47.04 beige

Special colours

Other colours from our clean-off collection also available.

Flammability

Insert with fire classification Cfl-s1 according to EN 13501.

Connection Plastic-coated stainless steel cable

Warranty 5 years guarantee

Warranty conditions are available at:

Insert certified to TÜV PROFICERT-

product interior (Standard)

French VOC regulation

LEED v4 (outside North America)

BREEAM Exemplary Level Belgian VOC regulation

AgBB (Committee for Health-related Evaluation of Building

Products)

MVV TB Appendix 8, 9 / ABG

Pile material 100% PA 6 (polyamide)

Use classification EN1307 class 33 (heavy commercial use)

Colour fastness to artificial light ISO



**105-B02** good 5-6

Colour fastness to rubbing ISO 105

X12

Dimensions

good 4-5

Colour fastness to water ISO 105 E01

good 4-5

good in the state of the state

Mat width:....mm (bar length)

Mat depth:....mm (walking direction)

Contact emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-

49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·

www.emco-bau.com