

emco Bau

emco DIPLOMAT Premium Large With Conform insert 522 PL Conform

Model	522 PL Conform
Load	Normal to heavy
Support chassis	Made using rigid aluminium with sound absorbing insulation on the underside
Support chassis colour	Standard natural anodized Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
Approx. height (mm)	22
Note on height	The insert can actually be approx. 2 mm higher due to the wear layer.
Tread surface	The Conform insert made of recycled materials is the perfect complement to wooden surroundings and can be used in a whole host of environments.
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile gaps, for revolving doors, available in 3mm according to DIN EN 16005
Slip resistance	R 12 slip resistance as per DIN 51130
Colours	Anthracite 76.01 Beige 76.02 Brown 76.04
Special colours	Other colours from our clean-off collection also available.
Flammability	Fire classification for the complete mat system Cfl-s1 in accordance with EN 13501
Connection	Plastic-coated stainless steel cable
Warranty	5 years guarantee Warranty conditions are available at:
Insert certified to TÜV PROFiCERT-product interior (Standard)	French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG
Pile material	100% PA 6 (polyamide)
Use classification EN1307	Property suitable inlay 33

Bacterial reduction EHEC ASTM-e2149 16,1 %

Bacterial reduction staphylococcus aureus ASTM-e2149 0,0 %

Bacterial reduction klebsiella pneumoniae ASTM-e2149 65,6 %

Dimensions

Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)

Contact

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com