

## emco Bau

### emco DIPLOMAT Premium Large With Conform insert 522 PL Conform

|                                                               |                                                                                                                                                                                                                   |
|---------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model                                                         | 522 PL Conform                                                                                                                                                                                                    |
| Load                                                          | Normal to heavy                                                                                                                                                                                                   |
| Support chassis                                               | Made using rigid aluminium with sound absorbing insulation on the underside                                                                                                                                       |
| Support chassis colour                                        | Standard natural anodized Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel                                                                                   |
| Approx. height (mm)                                           | 22                                                                                                                                                                                                                |
| Note on height                                                | The insert can actually be approx. 2 mm higher due to the wear layer.                                                                                                                                             |
| Tread surface                                                 | The Conform insert made of recycled materials is the perfect complement to wooden surroundings and can be used in a whole host of environments.                                                                   |
| Standard profile clearance approx. (mm)                       | 5 mm, rubber spacers                                                                                                                                                                                              |
| Automatic door systems                                        | Profile gaps, for revolving doors, available in 3mm according to DIN EN 16005                                                                                                                                     |
| Slip resistance                                               | R 12 slip resistance as per DIN 51130                                                                                                                                                                             |
| Colours                                                       | Anthracite 76.01<br>Beige 76.02<br>Brown 76.04                                                                                                                                                                    |
| Special colours                                               | Other colours from our clean-off collection also available.                                                                                                                                                       |
| Flammability                                                  | Fire classification for the complete mat system Cfl-s1 in accordance with EN 13501                                                                                                                                |
| Connection                                                    | Plastic-coated stainless steel cable                                                                                                                                                                              |
| Warranty                                                      | 5 years guarantee<br>Warranty conditions are available at:                                                                                                                                                        |
| Insert certified to TÜV PROFiCERT-product interior (Standard) | French VOC regulation<br>LEED v4 (outside North America)<br>BREEAM Exemplary Level<br>Belgian VOC regulation<br>AgBB (Committee for Health-related Evaluation of Building Products)<br>MVV TB Appendix 8, 9 / ABG |
| Pile material                                                 | 100% PA 6 (polyamide)                                                                                                                                                                                             |
| Use classification EN1307                                     | Property suitable inlay 33                                                                                                                                                                                        |

**Bacterial reduction EHEC ASTM-e2149** 16,1 %

**Bacterial reduction staphylococcus aureus ASTM-e2149** 0,0 %

**Bacterial reduction klebsiella pneumoniae ASTM-e2149** 65,6 %

**Dimensions**

Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)

**Contact**

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: [bau@emco.de](mailto:bau@emco.de) · [www.emco-bau.com](http://www.emco-bau.com)