

## emco Bau

### emco DIPLOMAT Premium Large With Conform insert and scraping edge 522 PL Conform K

<b>Model</b>	522 PL Conform K
<b>Load</b>	Normal to heavy
<b>Support chassis</b>	Made using aluminium with sound absorbing insulation on the underside
<b>Support chassis colour</b>	Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
<b>Approx. height (mm)</b>	22
<b>Tread surface</b>	The Conform insert made of recycled materials is the perfect complement to wooden surroundings and can be used in a whole host of environments. The additional profile increases the cleaning power.
<b>Standard profile clearance approx. (mm)</b>	5 mm, rubber spacers
<b>Revolving door drives</b>	Our mats with a profile spacing of 3mm in accordance with DIN EN 16005 are available for revolving door drives.
<b>Colours</b>	76.01 Anthracite 76.02 Beige 76.04 Brown
<b>Special colours</b>	Other colours from our clean-off collection also available.
<b>Flammability</b>	Insert with fire classification Cfl-s1 according to EN 13501.
<b>Connection</b>	Thanks to plastic-coated steel cable
<b>Warranty</b>	5 years guarantee Warranty conditions are available at:
<b>Insert certified to TÜV PROFiCERT-product interior (Standard)</b>	French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG
<b>Pile material</b>	100% PA 6 (polyamide)
<b>Use classification EN1307</b>	Property suitable inlay 33
<b>Dimensions</b>	Mat width:.....mm (bar length) Mat depth:.....mm (walking direction)



**BIM Data**

BIM Data is available to download from <https://www.emco-bau.com/pim/bim-daten-GER.zip>.

**Contact**

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 Email: [bau@emco.de](mailto:bau@emco.de) · [www.emco-bau.com](http://www.emco-bau.com)