

emco Bau

emco DIPLOMAT Premium Large With Innova insert 522 PL Innova

Model 522 PL Innova

Load Normal to heavy

Support chassis Made using rigid aluminium with Premium sound absorbing

insulation on the underside

Support chassis colour Aluminium as standard. Anodised colours for an additional

charge: EV3 gold, C33 mid-bronze, C35 black or C31

stainless steel

Approx. height (mm) 22

Tread surface The exceptionally flexible Innova insert not only creates a

sophisticated impression but also improves room acoustics.

Standard profile clearance approx.

(mm)

5 mm, rubber spacers

Automatic door systems Profile clearance of 3 mm available as an option for

revolving door drives, in accordance with EN 16005

Slip resistance R 12 slip resistance as per DIN 51130

Colours 36.02 anthracite

36.03 grey 36.01 black

Special colours Other colours from our clean-off collection also available.

Flammability Fire classification for the complete mat system Cfl-s1 in

accordance with EN 13501

Connection Plastic-coated stainless steel cable

Warranty 5 years guarantee

Warranty conditions are available at:

Insert certified to TÜV PROFICERT-

product interior (Standard)

French VOC regulation

LEED v4 (outside North America)

BREEAM Exemplary Level Belgian VOC regulation

AgBB (Committee for Health-related Evaluation of Building

Products)

MVV TB Appendix 8, 9 / ABG

Pile material 100% PA 6 (polyamide)

Use classification EN1307 class 33 (heavy commercial use)

Colour fastness to artificial light ISO

105-B02

good 5-6



Colour fastness to rubbing ISO 105 good 4-5

X12

Colour fastness to water ISO 105 E01 good 4-5

Bacterial reduction EHEC ASTM-e2149 8,4 %

Bacterial reduction staphylococcus

aureus ASTM-e2149

51,7 %

Bacterial reduction klebsiella

pneumoniae ASTM-e2149

83,6 %

Dimensions Mat width:....mm (bar length)

Mat depth:....mm (walking direction)

Contact emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-

49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·

www.emco-bau.com