

## emco Bau

### emco MARSCHALL Premium Large With MAXIMUS insert 522 PSL Maximus

|                                                               |                                                                                                                                                                                     |
|---------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model                                                         | 522 PSL Maximus                                                                                                                                                                     |
| Load                                                          | Extremely heavy                                                                                                                                                                     |
| Support chassis                                               | Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside                                                                              |
| Support chassis colour                                        | Standard natural anodized Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel                                                     |
| Approx. height (mm)                                           | 22                                                                                                                                                                                  |
| Note on height                                                | The insert can actually be approx. 2-3 mm higher due to the wear layer.                                                                                                             |
| Tread surface                                                 | Embedded, robust MAXIMUS inserts in Bfl-S1 quality (clean-off floor covering made from special polyamide yarn, 100%)                                                                |
| Standard profile clearance approx. (mm)                       | 5 mm, rubber spacers                                                                                                                                                                |
| Automatic door systems                                        | Profile gaps, for revolving doors, available in 3mm according to DIN EN 16005                                                                                                       |
| Slip resistance                                               | R 12 slip resistance as per DIN 51130                                                                                                                                               |
| Colours                                                       | Anthracite 80.02<br>Brown 80.04<br>Red 80.07<br>Black mottled 81.01<br>Black 80.01                                                                                                  |
| Special colours                                               | Other colours from our clean-off collection also available.                                                                                                                         |
| Flammability                                                  | Fire classification for the complete mat system Bfl-s1 in accordance with EN 13501                                                                                                  |
| Connection                                                    | Plastic-coated stainless steel cable                                                                                                                                                |
| Warranty                                                      | 5 years guarantee<br>Warranty conditions are available at:                                                                                                                          |
| Insert certified to TÜV PROFiCERT-product interior (Standard) | French VOC regulation<br>LEED v4 (outside North America)<br>BREEAM Exemplary Level<br>Belgian VOC regulation<br>AgBB (Committee for Health-related Evaluation of Building Products) |

MVV TB Appendix 8, 9 / ABG

**Pile material**

100% PA 6.6 (polyamide)

**Use classification EN1307**

Property suitable inlay 33

**Colour fastness to artificial light ISO 105-B02**

good 5-6

**Colour fastness to rubbing ISO 105 X12**

good 5

**Colour fastness to water ISO 105 E01**

good 5

**Bacterial reduction EHEC ASTM-e2149**

29,4 %

**Bacterial reduction staphylococcus aureus ASTM-e2149**

16,7 %

**Bacterial reduction klebsiella pneumoniae ASTM-e2149**

68,2 %

**Dimensions**

Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)

**Contact**

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · [www.emco-bau.com](http://www.emco-bau.com)