

emco Bau

emco MARSCHALL Premium With Care insert 522 PS Care

Model 522 PS Care

Load Extremely heavy

Support chassis Reinforced support chassis made using rigid aluminium with

Premium sound absorbing insulation on the underside

Support chassis colour Aluminium as standard. Anodised colours for an additional

charge: EV3 gold, C33 mid-bronze, C35 black or C31

stainless steel

Approx. height (mm) 22

Tread surface The robust and exceptionally abrasion-resistant Care insert

for the effective reduction of fine dirt.

Standard profile clearance approx.

(mm)

5 mm, rubber spacers

Automatic door systems Profile clearance of 3 mm available as an option for

revolving door drives, in accordance with EN 16005

Slip resistance R 12 slip resistance as per DIN 51130

Colours 47.01 anthracite

47.04 beige

47.03 brown

47.02 grey

Special colours Other colours from our clean-off collection also available.

Flammability Fire classification for the complete mat system Cfl-s1 in

accordance with EN 13501

Connection Plastic-coated stainless steel cable

Warranty 5 years guarantee

Warranty conditions are available at:

Insert certified to TÜV PROFICERT-

product interior (Standard)

French VOC regulation

LEED v4 (outside North America)

BREEAM Exemplary Level

Belgian VOC regulation

AgBB (Committee for Health-related Evaluation of Building

Products)

MVV TB Appendix 8, 9 / ABG

Pile material 100% PA 6 (polyamide)

Use classification EN1307 class 33 (heavy commercial use)

Colour fastness to artificial light ISO



105-B02 good 5-6 Colour fastness to rubbing ISO 105 good 4-5 X12 Colour fastness to water ISO 105 E01 good 4-5 Bacterial reduction EHEC ASTM-e2149 11,9 % **Bacterial reduction staphylococcus** 45,0 % aureus ASTM-e2149 Bacterial reduction klebsiella 99,8 % pneumoniae ASTM-e2149 Dimensions Mat width:....mm (bar length) Mat depth:....mm (walking direction) Contact emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·

www.emco-bau.com