

## emco Bau

### emco MARSCHALL Premium With Conform insert 522 PS Conform

|  |   |
|--|---|
| <b>Model</b>   | 522 PS Conform  |
| <b>Load</b>  | Extremely heavy   |
| <b>Support chassis</b>   | Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside  |
| <b>Support chassis colour</b>  | Standard natural anodized Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel   |
| <b>Approx. height (mm)</b>   | 22  |
| <b>Note on height</b>  | The insert can actually be approx. 2 mm higher due to the wear layer.   |
| <b>Tread surface</b>   | The Conform insert made of recycled materials is the perfect complement to wooden surroundings and can be used in a whole host of environments.   |
| <b>Standard profile clearance approx. (mm)</b>                       | 5 mm, rubber spacers  |
| <b>Automatic door systems</b>  | Profile gaps, for revolving doors, available in 3mm according to DIN EN 16005   |
| <b>Slip resistance</b>   | R 12 slip resistance as per DIN 51130   |
| <b>Colours</b>   | Anthracite 76.01<br>Beige 76.02<br>Brown 76.04  |
| <b>Special colours</b>   | Other colours from our clean-off collection also available.   |
| <b>Flammability</b>  | Fire classification for the complete mat system Cfl-s1 in accordance with EN 13501  |
| <b>Connection</b>  | Plastic-coated stainless steel cable  |
| <b>Warranty</b>  | 5 years guarantee<br>Warranty conditions are available at:  |
| <b>Insert certified to TÜV PROFiCERT-product interior (Standard)</b> | French VOC regulation<br>LEED v4 (outside North America)<br>BREEAM Exemplary Level<br>Belgian VOC regulation<br>AgBB (Committee for Health-related Evaluation of Building Products)<br>MVV TB Appendix 8, 9 / ABG |
| <b>Pile material</b>   | 100% PA 6 (polyamide)   |
| <b>Use classification EN1307</b>                                     | Property suitable inlay 33  |

**Bacterial reduction EHEC ASTM-e2149** 16,1 %

**Bacterial reduction staphylococcus aureus ASTM-e2149** 0,0 %

**Bacterial reduction klebsiella pneumoniae ASTM-e2149** 65,6 %

**Dimensions**

Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)

**Contact**

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: [bau@emco.de](mailto:bau@emco.de) · [www.emco-bau.com](http://www.emco-bau.com)