

emco Bau

emco MARSCHALL Premium With Outdoor insert 522 PS Outdoor

Model	522 PS Outdoor
Load	Extremely heavy
Support chassis	Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside
Support chassis colour	Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
Approx. height (mm)	22
Tread surface	The weather-resistant Outdoor insert for noticeably thorough removal of coarse dirt.
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Revolving door drives	Our mats with a profile spacing of 3mm in accordance with DIN EN 16005 are available for revolving door drives.
Slip resistance	R 11 slip resistance as per DIN 51130
Colours	Anthracite Brown Red
Flammability	Fire classification for the complete mat system Cfl-s1 in accordance with EN 13501
Connection	Thanks to plastic-coated steel cable
Warranty	5 years guarantee Warranty conditions are available at:
Pile material	100% PA 6 (polyamide)
Use classification EN1307	Property suitable inlay 33
Colour fastness to artificial light ISO 105-B02	excellent 7
Colour fastness to rubbing ISO 105 X12	good 4-5
Colour fastness to water ISO 105 E01	good 4-5
Bacterial reduction EHEC ASTM-e2149	22,4 %
Bacterial reduction staphylococcus aureus ASTM-e2149	17,3 %
Bacterial reduction klebsiella pneumoniae ASTM-e2149	9,8 %
Dimensions	Mat width:.....mm (bar length) Mat depth:.....mm (walking direction)



BIM Data

BIM Data is available to download from <https://www.emco-bau.com/pim/bim-daten-GER.zip>.

Contact

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 Email: bau@emco.de · www.emco-bau.com