

## emco Bau

### emco DIPLOMAT Premium With Care insert and brush strip 522 P Care B

<b>Model</b>	522 P Care B
<b>Load</b>	Normal to heavy
<b>Support chassis</b>	Made using rigid aluminium with Premium sound absorbing insulation on the underside
<b>Support chassis colour</b>	Aluminium as standard. Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
<b>Approx. height (mm)</b>	22
<b>Tread surface</b>	The robust and exceptionally abrasion-resistant Care insert for the effective reduction of fine dirt. The additional profile increases the cleaning power.
<b>Standard profile clearance approx. (mm)</b>	5 mm, rubber spacers
<b>Automatic door systems</b>	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005
<b>Colours</b>	47.01 anthracite 47.02 grey 47.03 brown 47.04 beige grey Black
<b>Special colours</b>	Other colours from our clean-off collection also available.
<b>Flammability</b>	Insert with fire classification Cfl-s1 according to EN 13501.
<b>Connection</b>	Plastic-coated stainless steel cable
<b>Warranty</b>	5 years guarantee Warranty conditions are available at:
<b>Pile material</b>	100% PA 6 (polyamide)
<b>Use classification EN1307</b>	class 33 (heavy commercial use)
<b>Colour fastness to artificial light ISO 105-B02</b>	good 5-6
<b>Colour fastness to rubbing ISO 105 X12</b>	good 4-5
<b>Colour fastness to water ISO 105 E01</b>	good 4-5
<b>Dimensions</b>	Mat width:.....mm (bar length) Mat depth:.....mm (walking direction)

## Contact

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-  
49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-  
500 · Fax: +49 (0) 591/9140-852 · Email: [bau@emco.de](mailto:bau@emco.de) ·  
[www.emco-bau.com](http://www.emco-bau.com)