

## emco Bau

### emco DIPLOMAT Premium With Maximus insert and brush strip 522 P Maximus B

|   |   |
|---|---|
| Model   | 522 P Maximus B   |
| Load  | Normal to heavy   |
| Support chassis   | Made using rigid aluminium with Premium sound absorbing insulation on the underside   |
| Support chassis colour  | Aluminium as standard. Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel  |
| Approx. height (mm)   | 22  |
| Tread surface   | The stylish Maximus insert stands out from the crowd with its premium-quality tufted velour and high-end design. The additional profile increases the cleaning power.   |
| Standard profile clearance approx. (mm)                       | 5 mm, rubber spacers  |
| Automatic door systems  | Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005   |
| Colours   | Anthracite 80.02<br>Brown 80.04<br>Red 80.07<br>Black mottled 81.01<br>Black 80.01<br>grey<br>Black   |
| Special colours   | Other colours from our clean-off collection also available.   |
| Flammability  | Insert with fire classification Bfl-s1 according to EN 13501.   |
| Connection  | Plastic-coated stainless steel cable  |
| Warranty  | 5 years guarantee<br>Warranty conditions are available at:  |
| Insert certified to TÜV PROFiCERT-product interior (Standard) | French VOC regulation<br>LEED v4 (outside North America)<br>BREEAM Exemplary Level<br>Belgian VOC regulation<br>AgBB (Committee for Health-related Evaluation of Building Products)<br>MVV TB Appendix 8, 9 / ABG |

|                                  |   |
|----------------------------------|---|
| <b>Pile material</b>             | 100% PA 6.6 (polyamide)   |
| <b>Use classification EN1307</b> | class 33 (heavy commercial use)   |
| <b>Dimensions</b>                | Mat width:.....mm (bar length)<br>Mat depth:.....mm (walking direction)   |
| <b>Contact</b>                   | emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-<br>49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-<br>500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·<br>www.emco-bau.com |