

emco Bau

emco RADIAL With ribbed carpet insert 522 RDR

Model	522 RDR
Load	Extremely heavy
Support chassis	Made using rigid aluminium with sound absorbing insulation on the underside
Approx. height (mm)	22
Tread surface	Recessed, robust, weather-proof, ribbed carpet strips.
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile gaps, for revolving doors, available in 3mm according to DIN EN 16005
Colours	Light grey no. 220 Anthracite no. 200 Red no. 305 Brown no. 485 Sand no. 430
Special colours	Standard ribbed carpet colours: Light grey, anthracite, beige, blue. Special colours available: mauve, blue/grey, red, brown, turquoise, royal blue, sand and grape
Flammability	Insert for Light Grey and Anthracite ribbed carpet colours available on request (surcharge applicable) with fire classification Cfl-s1 according to EN 13501.
Connection	Threaded stainless steel rod
Colour fastness to artificial light ISO 105-B02	good 6
Colour fastness to rubbing ISO 105 X12	good 4
Colour fastness to water ISO 105 E01	good 5
Dimensions	Mat width:.....mm (bar length) Mat depth:.....mm (walking direction)
Contact	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com