
Model 522 SLRK





The extra-wide original entrance mat with the effective, coarse-fibre rib insert is exceptionally abrasion resistant and offers maximum dimensional stability. Particularly ideal for collecting fine dirt. The additional profile offers even more cleaning power. Optimally designed for buildings exposed to extreme footfall.







Indoor and outdoor (covered, Zone 1+2)

Description

Roll-up, extremely hard-wearing Original entrance mat with extra-wide profiles and Standard insert for surface installation. Customisable width and depth without alignment profile. Available in any geometric shape.









Street dust, hair, sand, ash, ranty textile fibres, small leaves and twigs, etc.



4 year war-



Model 522 SLRK

Approx. height (mm)	22
Roll-over and drive-over capability:	Prams
	Sack-/hand truck
	Wheelchairs
Standard profile	5 mm, rubber spacers
clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile clearance of 3 mm available as an option for revolving door drives, in
	accordance with EN 16005
Connection	Plastic-coated steel cable
Max. width/profile length for individual	3000
section (mm):	3000
Profile width (mm)	46.5
Depth/walking depth for individual section	000
(mm):	800
Weight (kg/m²)	14.1
	From a profile length of 3000 mm
Mat division as per factory standards	or a maximum mat weight of 30 kg. For profile lengths above 2300 mm, a
ractory standards	surcharge is applicable. Mat devisions/ splits possible at customer's request.
Support chassis	Reinforced support chassis made using
	rigid aluminium with sound absorbing insulation on the underside
	Aluminium as standard. Anodised
Support chassis colour	colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31
	stainless steel
Tread surface	Recessed, robust, weather-proof, ribbed
	carpet strips, also with scraper bars mounted between the profiles.
Flammability	Insert available on request (surcharge
	applicable) with fire classification Cfl-s1 according to EN 13501.
Pile material	100% PP (polypropylene)
Colour fastness to	
artificial light ISO 105- B02	good 6
Colour fastness to	good 4
rubbing ISO 105 X12	
Colour fastness to water ISO 105 E01	good 5

Accessories	
1	
emco installation frame 500: 500-25 AL Aluminium	
emco installation frame 500: 500-25 CN Chrome-nickel steel (V2A)	
emco LUMINA: LUMINA Aluminium	
emco LUMINA: LUMINA + LED Aluminium	
emco LUMINA: LUMINA VIA Aluminium	
emco ramp edge: A17 Aluminium	
emco T-profile: T22	
emco cover strip: C22 Chrome-nickel steel (V2A)	
emco INOX®: LINEO 22 Chrome-nickel steel (V2A)	
emco INOX®: QUADRO 22 Chrome-nickel steel (V2A)	
emco dirt collection well: 5522AL Aluminium	
emco dirt collection well: 5522CN Chrome-nickel steel (V2A)	
emco dirt collection well: 5522AL Aluminium	
emco dirt collection well: 5522CN Chrome-nickel steel (V2A)	
Rubber underlay 3 mm: GU 3	
Rubber underlay 5 mm: GU 5	
Rubber underlay 1 mm: GU 1	
Mat joining brackets: MV Supplied as standard with mats in several parts	



Sports hall

Model 522 SLRK

Suitable for:
Retirement homes and Care-/Nursery Homes
Arena
medical practice
Train station
DIY store
Offices and administrative buildings
Family home
Shopping centre
Retail sector
University / Higher education institution
airport
Hotel
Industry
Kindergarten/Nursery
Warehouse
Apartment building
Trade fair
School

Insert certified to TÜV PROFICERT- product interior (Standard)

French VOC regulation

LEED v4 (outside North America)

BREEAM Exemplary Level

Belgian VOC regulation

AgBB (Committee for Health-related Evaluation of Building Products)

MVV TB Appendix 8, 9 / ABG

Service and services
Construction site advice
Dimensioning
Measured using laser measuring device on site.
Installation service
Fitting and installation service
Repairs
The product can be disposed of or recycled in an environmentally friendly way.




Model 522 SLRK

Colours



Light grey no. 220



Red no. 305



Warranty conditions are available at: www.emco-bau.com/en/warranty-conditions/

Subject to technical modifications



Anthracite no. 200



