

emco Bau

emco MARSCHALL Premium With MAXIMUS insert 522 TLS PS Maximus

Model	522 TLS PS Maximus
Load	Extremely heavy
Support chassis	made of rigid aluminium with sound insulation underlay. In the area of the tactile guidance system, the profiles are laid alternately in two heights.
Approx. height (mm)	22
Note on height	The insert can actually be approx. 2-3 mm higher due to the wear layer.
Tread surface	Recessed, robust, weather-proof coarse fibre ribbed carpet strips (brand-name fibres) for even better dirt removal.
Standard profile clearance approx. (mm)	3 mm, rubber spacers
Colours	Anthracite 80.02 Beige mottled 81.05 Grey 80.03 Black mottled 81.01 Black 80.01
Connection	With threaded rod
Warranty	5 years guarantee
Pile material	100% PA 6 (polyamide)
Colour fastness to artificial light ISO 105-B02	good 5-6
Colour fastness to rubbing ISO 105 X12	good 5
Colour fastness to water ISO 105 E01	good 5
Dimensions	Mat width:.....mm (bar length) Mat depth:.....mm (walking direction)
Contact	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 Email: bau@emco.de · www.emco-bau.com