

emco Bau

emco DIPLOMAT Premium With Care insert 522 TLS P Care

Model 522 TLS P Care

Load Normal to heavy

Support chassis made of rigid aluminium with sound insulation underlay. In

the area of the tactile guidance system, the profiles are laid

alternately in two heights.

Approx. height (mm) 22

Tread surface The robust and exceptionally abrasion-resistant Care insert

for the effective reduction of fine dirt.

Standard profile clearance approx.

(mm)

3 mm, rubber spacers

Colours 47.01 anthracite

47.02 grey 47.03 brown 47.04 beige

ConnectionWith threaded rodWarranty5 years guarantee

Warranty conditions are available at:

Pile material 100% PA 6 (polyamide)

Colour fastness to artificial light ISO

105-B02

good 5-6

Colour fastness to rubbing ISO 105

X12

good 4-5

Colour fastness to water ISO 105 E01 go

good 4-5

Dimensions Mat width:....mm (bar length)

Mat depth:....mm (walking direction)

Contact emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-

49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·

www.emco-bau.com