

## emco Bau

### emco DIPLOMAT Premium With Outdoor insert 522 TLS P Outdoor

<b>Model</b>	522 TLS P Outdoor
<b>Load</b>	Normal to heavy
<b>Support chassis</b>	made of rigid aluminium with sound insulation underlay. In the area of the tactile guidance system, the profiles are laid alternately in two heights.
<b>Approx. height (mm)</b>	22
<b>Tread surface</b>	The weather-resistant Outdoor insert for noticeably thorough removal of coarse dirt.
<b>Standard profile clearance approx. (mm)</b>	3 mm, rubber spacers
<b>Colours</b>	Anthracite Brown Red
<b>Connection</b>	With threaded rod
<b>Warranty</b>	5 years guarantee Warranty conditions are available at:
<b>Pile material</b>	100% PA 6 (polyamide)
<b>Colour fastness to artificial light ISO 105-B02</b>	excellent 7
<b>Colour fastness to rubbing ISO 105 X12</b>	good 4-5
<b>Colour fastness to water ISO 105 E01</b>	good 4-5
<b>Dimensions</b>	Mat width:.....mm (bar length) Mat depth:.....mm (walking direction)
<b>Contact</b>	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 Email: bau@emco.de · www.emco-bau.com