

## emco Bau

### emco PLAZA With rubber insert 542 SG

<b>Model</b>	542 SG
<b>Load</b>	Exceptionally heavy
<b>Support chassis</b>	Thick-walled, rigid aluminium with impact sound insulation underlay
<b>Approx. height (mm)</b>	42
<b>Tread surface</b>	Recessed, robust, weather-proof profiled rubber inserts.
<b>Standard profile clearance approx. (mm)</b>	5 mm, rubber spacers
<b>Automatic door systems</b>	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005
<b>Colours</b>	black
<b>Flammability</b>	Complete mat system available on request (surcharge applicable) with fire classification Bfl-s1 according to EN 13501.
<b>Connection</b>	Plastic-coated steel cable
<b>Warranty</b>	4 year warranty Warranty conditions are available at:
<b>Dimensions</b>	Mat width:.....mm (bar length) Mat depth:.....mm (walking direction)
<b>Contact</b>	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com