

## emco Bau

### emco PLAZA With ribbed carpet insert 542 SR

|                                                 |                                                                                                                                                                                                                          |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model                                           | 542 SR                                                                                                                                                                                                                   |
| Load                                            | Exceptionally heavy                                                                                                                                                                                                      |
| Support chassis                                 | Thick-walled, rigid aluminium with impact sound insulation underlay                                                                                                                                                      |
| Approx. height (mm)                             | 42                                                                                                                                                                                                                       |
| Tread surface                                   | Recessed, robust, weather-proof coarse fibre ribbed carpet strips (brand-name fibres) for even better dirt removal.                                                                                                      |
| Standard profile clearance approx. (mm)         | 5 mm, rubber spacers                                                                                                                                                                                                     |
| Automatic door systems                          | Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005                                                                                                                  |
| Colours                                         | Light grey no. 220<br>Anthracite no. 200<br>Red no. 305<br>Brown no. 485<br>Sand no. 430                                                                                                                                 |
| Flammability                                    | Insert for Light Grey and Anthracite ribbed carpet colours available on request (surcharge applicable) with fire classification Cfl-s1 according to EN 13501.                                                            |
| Connection                                      | Plastic-coated steel cable                                                                                                                                                                                               |
| Warranty                                        | 4 year warranty<br>Warranty conditions are available at:                                                                                                                                                                 |
| Colour fastness to artificial light ISO 105-B02 | good 6                                                                                                                                                                                                                   |
| Colour fastness to rubbing ISO 105 X12          | good 4                                                                                                                                                                                                                   |
| Colour fastness to water ISO 105 E01            | good 5                                                                                                                                                                                                                   |
| Dimensions                                      | Mat width:.....mm (bar length)<br>Mat depth:.....mm (walking direction)                                                                                                                                                  |
| Contact                                         | emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · <a href="http://www.emco-bau.com">www.emco-bau.com</a> |