Model COLOR PLUS





The perfect addition to a comprehensive range. Made from highquality tufted velour. Wide range of uses in public buildings and private apartments due to its combination of mottled colours.







Indoor areas (zone 3)

Description

With its surface structure that is able to conceal dirt and its blends of different colours, COLOR PLUS is the perfect solution for protecting textile, stone or parquet floors that lie beyond the clean-off zone. COLOR PLUS prevents dirt and moisture from outside the building being brought in.





Cfl-s1







Suitable for stairs



DS (EN 13893) Resistant strength



High



Property suitable inlay 32



Model COLOR PLUS

| Construction | Tufting velour 5/32" |
|---------------------------------|--|
| Pile above substrate | 100% polyamide |
| Substrate material | Polyester fleece |
| Backing material | Heavy coating |
| Pile weight / fibre weight | 850 |
| Total weight (g/m²) | 3.450 |
| Overall height (mm) | 8 |
| Tuft density/m ² | 83.150 |
| Slip resistance | DS (EN 13893) |
| | |
| Certificates | CE conformity EN 14041 (rolls only) |
| Certificates | CE conformity EN 14041 (rolls only) 90 cm wide (incl. border) |
| Certificates Supplied as rolls | , |
| | 90 cm wide (incl. border) |
| | 90 cm wide (incl. border) 130 cm wide (incl. border) |
| Supplied as rolls | 90 cm wide (incl. border) 130 cm wide (incl. border) 200 cm wide (incl. border) |
| | 90 cm wide (incl. border) 130 cm wide (incl. border) 200 cm wide (incl. border) 60 x 90 cm (incl. border) |
| Supplied as rolls | 90 cm wide (incl. border) 130 cm wide (incl. border) 200 cm wide (incl. border) 60 x 90 cm (incl. border) 90 x 120 cm (incl. border) |

| Laying | Individual rolls or smaller coverings can be laid loose on any smooth floor. For larger areas, and allowing for on-site conditions, we recommend fixed laying with an adhesive suitable for plasticised PVC. |
|----------|---|
| Cleaning | Dirt removal with powerful brush vacuum cleaner. The spray extraction process is recommended for periodic basic cleaning. Cleaning with plenty of water is absolutely no problem, water temperature should not be above 40°C. Do not use chlorinated hydrocarbon (Tetra). |
| Brand | emco |

| Suitable for: |
|--|
| Retirement homes and Care-/Nursery Homes |
| medical practice |
| Offices and administrative buildings |
| Family home |
| Hotel |
| Kindergarten/Nursery |
| Apartment building |
| School |
| Sports hall |



Model COLOR PLUS

Colours













